



1

| | | | | | | | | | | | |
|---|-----|---|------|---|-------------|--------------|------------------|-----------|-----------|--|--|
| Palm pushbutton Ø30 2 positions | 3/2 | Ordering code 228.1.7.1/C | 5/2 | Palm pushbutton Ø30 2 positions | | | | | | | |
| | | <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>TYPE</td></tr> <tr><td>1 32 = 3 ways</td></tr> <tr><td>52 = 5 ways</td></tr> <tr><td>BUTTON COLOR</td></tr> <tr><td>C 1 = Red</td></tr> <tr><td>2 = Black</td></tr> <tr><td>3 = Green</td></tr> </table> | TYPE | 1 32 = 3 ways | 52 = 5 ways | BUTTON COLOR | C 1 = Red | 2 = Black | 3 = Green | | |
| TYPE | | | | | | | | | | | |
| 1 32 = 3 ways | | | | | | | | | | | |
| 52 = 5 ways | | | | | | | | | | | |
| BUTTON COLOR | | | | | | | | | | | |
| C 1 = Red | | | | | | | | | | | |
| 2 = Black | | | | | | | | | | | |
| 3 = Green | | | | | | | | | | | |
| <p>Weight gr. 148 Operating force 33N</p> | | | | <p>Weight gr. 168 Operating force 33N</p> | | | | | | | |

| Operational characteristic | | | | | |
|-----------------------------|----------------------------|----------------|---------------------------------------|-------------------|--------------------|
| Fluid | Max working pressure (bar) | Temperature °C | Flow rate at 6 bar with Δp=1 (Nl/min) | Orifice size (mm) | Working ports size |
| Filtered and lubricated air | 10 bar | -5 - +70 | 540 Nl/min | mm 6 | G 1/8" |

| | | | | | | | | | | | |
|---|-----|---|------|---|-------------|--------------|------------------|-----------|-----------|--|--|
| Push button - Spring | 3/2 | Ordering code 228.1.8.1/C | 5/2 | Push button - Spring | | | | | | | |
| | | <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>TYPE</td></tr> <tr><td>1 32 = 3 ways</td></tr> <tr><td>52 = 5 ways</td></tr> <tr><td>BUTTON COLOR</td></tr> <tr><td>C 1 = Red</td></tr> <tr><td>2 = Black</td></tr> <tr><td>3 = Green</td></tr> </table> | TYPE | 1 32 = 3 ways | 52 = 5 ways | BUTTON COLOR | C 1 = Red | 2 = Black | 3 = Green | | |
| TYPE | | | | | | | | | | | |
| 1 32 = 3 ways | | | | | | | | | | | |
| 52 = 5 ways | | | | | | | | | | | |
| BUTTON COLOR | | | | | | | | | | | |
| C 1 = Red | | | | | | | | | | | |
| 2 = Black | | | | | | | | | | | |
| 3 = Green | | | | | | | | | | | |
| <p>Weight gr. 120 Operating force 33N</p> | | | | <p>Weight gr. 140 Operating force 33N</p> | | | | | | | |

| Operational characteristic | | | | | |
|-----------------------------|----------------------------|----------------|---------------------------------------|-------------------|--------------------|
| Fluid | Max working pressure (bar) | Temperature °C | Flow rate at 6 bar with Δp=1 (Nl/min) | Orifice size (mm) | Working ports size |
| Filtered and lubricated air | 10 bar | -5 - +70 | 540 Nl/min | mm 6 | G 1/8" |

| | | | | | | | | | | | |
|---|-----|---|------|---|-------------|--------------|------------------|-----------|-----------|--|--|
| Push button 2 positions | 3/2 | Ordering code 228.1.8/C | 5/2 | Push button 2 positions | | | | | | | |
| | | <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>TYPE</td></tr> <tr><td>1 32 = 3 ways</td></tr> <tr><td>52 = 5 ways</td></tr> <tr><td>BUTTON COLOR</td></tr> <tr><td>C 1 = Red</td></tr> <tr><td>2 = Black</td></tr> <tr><td>3 = Green</td></tr> </table> | TYPE | 1 32 = 3 ways | 52 = 5 ways | BUTTON COLOR | C 1 = Red | 2 = Black | 3 = Green | | |
| TYPE | | | | | | | | | | | |
| 1 32 = 3 ways | | | | | | | | | | | |
| 52 = 5 ways | | | | | | | | | | | |
| BUTTON COLOR | | | | | | | | | | | |
| C 1 = Red | | | | | | | | | | | |
| 2 = Black | | | | | | | | | | | |
| 3 = Green | | | | | | | | | | | |
| <p>Weight gr. 120 Operating force 10N</p> | | | | <p>Weight gr. 140 Operating force 10N</p> | | | | | | | |

| Operational characteristic | | | | | |
|-----------------------------|----------------------------|----------------|---------------------------------------|-------------------|--------------------|
| Fluid | Max working pressure (bar) | Temperature °C | Flow rate at 6 bar with Δp=1 (Nl/min) | Orifice size (mm) | Working ports size |
| Filtered and lubricated air | 10 bar | -5 - +70 | 540 Nl/min | mm 6 | G 1/8" |